

Availability is scheduled for calendar week 52 / 2015, from the Holzminden warehouse.

10. Main selling points | Product images

PER 18/21/24

- > Electronically controlled appliance for accurate temperature delivery at all times – maximum DHW convenience
- > Remote control included
- > Accurate temperature selection thanks to easy-to-read multifunction display with 2-colour backlighting
- > Dynamic flow rate regulation for precise temperatures at all times
- > 2 x temperature memory keys and economy mode
- > Selectable output (18/21/24)
- > Electronic air bubble detection
- > Bare wire heating system for soft and hard water areas
- > Integrated diagnostic system
- > Can also be installed with plastic pipes
- > Protection rating IP 25
- > Temperature selection range – 30 to 60 °C
- > Easy and fast installation
- > Suitable for solar operation with inlet temperatures up to 60 °C



PEO 18/21/24; 27

- > Electronic instantaneous water heater for optimum temperature convenience
- > Accurate temperature selection (30 – 60 °C) thanks to easy-to-read, two-colour LCD
- > At temperatures > 43 °C, the colour of the display changes from blue to red, to indicate a risk of scalding.
- > Bare wire heating system for soft and hard water areas
- > Suitable for solar operation with inlet temperatures up to 60 °C; reheating up to 45 °C
- > Protection rating IP 25
- > Integrated diagnostic system
- > Electronic air bubble detection
- > Selectable output
- > Easy and fast installation

